



Acetone

HANDLING

- Do not handle or open near flame, sources of heat, or sources of ignition.

STORAGE

- Store locked up. Store in a well-ventilated place. Keep container tightly closed.

DISPOSAL

- Dispose of contents/container to an approved waste disposal plant.



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Odor	Sweet, Solvent
Specific Gravity	0.79
Flash Point	-20° C (-4° F) Closed Cup
Boiling Point / Range	56.1° C (132.8° F)
Melting / Freezing Point	-94.7° C (-139° F)
Vapor Pressure	30.93 kPa at 25°C
Partition Coefficient	-0.24
Evaporation Rate	5.6 BuAc
Vapor Density	2
Auto-Ignition Temperature	465° C (869° F)
VOC Content	0%

AVAILABLE IN

Net Contents	Container Type	Units/Case	Part #
1 gal	pail	4	85738
5 gal	pail	1	85838



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved