



FG-2000

Foodgrade High Performance Metal Cutting Fluid

FEATURES

- Moderate to heavy-duty
- Vegetable-based, biodegradable lubricant
- For ferrous & nonferrous metals, aluminum and titanium
- Clean before heat treating with soap and water

APPLICATIONS

- General machining, sawing and cutting
- Food-grade applications
- Medical device manufacturing
- Swiss style CNC machining centers
- Milling, drilling and tapping

HANDLING

Avoid contact with skin, eyes, clothing. Wash thoroughly after handling.

STORAGE

Keep container tightly closed in a dry and well-ventilated place.

SPECIFICATIONS AND APPROVALS

- NSF International, H1



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Odor	Mild
Flash Point	> 399.2 °F (> 204 °C)
Boiling Point / Range	> 399.2 °F (> 204 °C)
Water Solubility	Insoluble.
Specific Gravity	0.92
VOC Content	0.2 g/L
Flash Point	608°F (320°C)
Pour Point	-4°F (-20°C)
Viscosity	40 cSt @ 40°C

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Color
FG2001	1 gal	bottle	4	gold
FG2055	55 gal	drum	1	gold



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved