



# High Temp Marker

## HANDLING

- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
- Not approved for repair of oven liners or other food contact surfaces. This product is not NSF registered or approved.

## STORAGE

- Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## DISPOSAL

- Dispose of contents/container in accordance with local/regional/national/international regulations.

## FEATURES

- Fiber tip paint marker with valve-action
- Valve-action mechanism prevents paint in barrel from drying when cap is left off
- Threaded barrel allows marker to be screwed into a jig or apparatus
- Drying time: 45 seconds - 1 minute



## PHYSICAL PROPERTIES

Appearance / Physical State	Liquid.
Prop 65 Warning	YES
Temperature Range	Blue: 2000°F (1093°C) White: 1550 - 1650°F (848 - 899°C) Black: 2000°F (1093°C) Green: 1800°F (982°C) Yellow: 800 - 900°F (426 - 482°C)

## AVAILABLE IN

Units/Case	Marker Tip	Color	Part #
48	medium, felt (#38)	blue	44094
48	medium, felt (#38)	white	44219
48	medium, felt (#38)	black	44250
48	medium, felt (#38)	green	44266
48	medium, felt (#38)	yellow	44424



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved