

# Accu-Lube® Synthetic General Purpose MQL

## FEATURES

- Replacement for straight oil
- Multi-purpose
- Water-based, synthetic lubricant
- Cools like flood coolant, lubricates like straight oil
- Rapid heat dissipation
- Clean before heat treating with rinse water

## APPLICATIONS

- General machining, sawing and cutting
- For ferrous metals

## DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

## HANDLING

Do not get in eyes. Wear eye protection/ face protection

## STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated place.

## DISPOSAL

Dispose of in accordance with local regulations.



## PHYSICAL PROPERTIES

<b>Appearance / Physical State</b>	Liquid.
<b>Odor</b>	Mild.
<b>Color</b>	Blue.
<b>pH Value</b>	8.6
<b>Flash Point</b>	>212.0°F (>100.0°C)
<b>Water Solubility</b>	Soluble.
<b>Specific Gravity</b>	1.04
<b>VOC Content</b>	0% per US State and Federal Consumer Product Regulations
<b>Pour Point</b>	30°F (-1°C)
<b>Viscosity</b>	8 cSt @ 40°C

## AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LBSYNT01	1 gal	bottle	4	36 lbs
LBSYNT55	55 gal	drum	1	499 lbs



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved